



Product code:	OL004
Sign size:	128x15
Lighting type:	Daylight viewable LEDs
Weight:	6.5 kg
DDA compliant:	Side
Maximum character height:	155mm
Static characters:	3 No & 15 characters+
Scrolling text:	1 & 2 lines



Case dimensions: W1286mm x H210mm x D50mm
Viewing area: W1234mm x H155mm

No	Part No	Product Code	Description	Qty
1	5029-20-01		128*15 LED CASE	1
2	5029-20-02		128*15 LEFT REAR COVER	1
3	5029-20-03		128*15 RIGHT REAR COVER	1
4	5029-20-04		128*15 CENTRE REAR COVER	1
5	7515-01-01	PC079	32*15 LED DISPLAY BOARD (AMBER LED)	4
6	7517-01-01	PC081	LED SIGN 3V POWER SUPPLY	4
7	7518-01-01	PC082	OUTSIDE LED 5V PSU SINGLE SIDE	1
8	7519-20-01	PC083	OUTSIDE LED SIGN INTERCONNECT PCB	3
9	7522-01-01	PC085	AMBIENT LIGHT SENSOR	1
10	7564-01-01	PC136	SUPER MOOSE PSU	1
11	7611-01-01	PC161	OUTSIDE LED MK2 SIGN PROCESSOR	1
12	0007-05-03		260MM 5-WAY AMP POWER CABLE	1
13	0006-05-01		8W-45MM MOLEX CABLE ASSY	3
14	0006-05-04		8W-340MM MOLEX CABLE ASSY	1
15	0001-05-04		14W-190MM MOLEX CABLE ASSY	1

TECHNICAL INFORMATION

Operating voltage	18 – 32 volts DC
Normal operating power consumption (33% LEDs on)	0.8 amps @ 24v DC (19 watts approx)
Max power consumption (all LEDs on full brightness)	2.2 amps @ 24v DC (53 watts approx)
Standard communications	RS 485 – other options available
Temperature range	-20C to + 60C
Storage temperature range	-20C to + 80C
LED pitch	Horizontal - 9.7mm / Vertical - 10.2mm
Humidity (operating)	95% max
Shock	10g max /11ms/3 axes
Vibration	1g/5-100 Hz/3 axes

NB: Power consumption will vary according to the message displayed. Environmental test information is taken from the results obtained from testing products based on a similar design.



Certified Supplier No 816
ISO 14001:2004

Hanover Displays Ltd, Unit 24, Cliffe Industrial Estate, Lewes,
East Sussex, BN8 6JL.
Tel: +44 (0)1273 477528 Fax: +44 (0)1273 407766



Certified Supplier No 816
ISO 9001: 2008